



TANDBERG Movi™

Turn your PC into a videoconferencing system. Movi enables PC users with a webcam to join an enterprise-wide video-conferencing network and communicate visually with colleagues for enhanced productivity from anywhere they need to work — the airport, hotel, coffee shop or home office.



As a centralized network device, Movi enables IT professionals to rapidly deploy PC-based videoconferencing to the entire organization.

DESIGN FEATURES

- Extend video to the PC for the entire enterprise
- Centralized network device for one-touch deployment and management
- 1U rack mountable
- LCD panel for easy installation

APPLICATION FEATURES

- Initiate ad hoc or scheduled video calls while on the go
- Enable video from anywhere
- Intuitive user interface
- Integrates into a full enterprise video network

PERFORMANCE FEATURES

- SIP up to 768kbps per active concurrent call
- Administrative control for call bandwidth
- Full duplex audio with audio mute capability
- No software installation required on individual PCs

PROTECT YOUR TECHNOLOGY INVESTMENT WITH TANDBERG'S PORTFOLIO OF **CONSTANT CARE SERVICES**. VISIT WWW.TANDBERG.COM



MOVI

BANDWIDTH
SIP up to 768 kbps

VIDEO
H.263
Picture in Picture (PIP)
SIF (352 x 240 pixels)
CIF (352 x 288 pixels)

AUDIO
G.711, G.722
Echo cancellation
Full Duplex Audio

PRIVACY FEATURE
Headset and microphone via PC
Audio Privacy (mute)

IP NETWORK FEATURES
DTMF
URI Dialing
Integrates with your existing SIP infrastructure

DIRECTORY SERVICES
Support for Local Directories (All registered Movi Clients)
Phonebooks distributed from TMS
Placed Calls with Date and Time



MOVI SERVER

BANDWIDTH CONTROL

SYSTEM MANAGEMENT
Management via embedded web-server or through SSH
Administration Password
Integrates with your existing SIP infrastructure

NETWORK INTERFACES
4 x Ethernet (10/100/1000 Mbit)

ETHERNET CONNECTIVITY
TCP/IP, SSH, HTTP
Embedded web-server

ENVIRONMENTAL DATA
Operating temperature: 0° C to 40° C (32° F to 104° F)
Relative humidity: 10% to 90%
Storage and transport temperature:
-20° C to 80° C (-4° F to 140° F) non-condensing

POWER
100-240VAC, 50-60Hz, 250W max

PHYSICAL DIMENSIONS
Height: 1.7" (44mm)
Width: 16.8" (426mm)
Depth: 16.4" (419mm)
19" rack-mountable, 1U height

APPROVALS
Directive 73/23/EEC (Low Voltage Directive)
Standard EN 60950-1
Directive 89/336/EEC (EMC Directive)
Standard EN 55022, Class A
Standard EN 55024
Standard EN 61000-3-2/-3-3
Directive 1999/5/EEC (R&TTE Directive)
Standard TBR 4
Approved according to UL 60950-1 and CAN/CSA C22.2
No. 60950-1-03
Complies with FC C15B Class A

All specifications subject to change without notice, system specifics may vary.

All images in these materials are for representational purposes only, actual products may differ.

TANDBERG and Movi are registered trademarks or trademarks of TANDBERG in the U.S. and other countries.

TANDBERG

Movi™

TANDBERG World Headquarters
Philip Pedersens vei 20
1366 Lysaker, Norway
Tel: +47 67 125 125
Fax: +47 67 125 234
Video: +47 67 126 126
tandberg@tandberg.com

1212 Avenue of the Americas,
24th Floor
New York, NY USA 10036
Tel: +1 212 692 6500
Fax: +1 212 692 6501
Video: +1 212 692 6535
tandberg@tandberg.com

May 2007

